

GBLP flexible packaging bag special type

Selection of pad assembly

Example: **GBLP - 30 - S - T1**

① Diameter of suction cup ② Material of suction cup

GBLP - 30 - S - 02M - T1

① Diameter of suction cup ② Material of suction cup ③ Installation method ④ Plug

① Diameter of suction cup ② Material of suction cup ③ Installation method

code	30	40	50
Disc diameter	Ø30	Ø40	Ø50

code	02M	03M	04M
External thread	G1/4	G3/8	G1/2


② Material of suction cup

code	texture of material	hardness ShoreA	Operating temperature range	colour	Applicable diameter of suction cup
S	silicon rubber	A40/S	-50~220°C	Light blue	Ø30~Ø50
FS	Fluorosilicone rubber	A55/S	-30~180°C	red	Ø30~Ø50

④ Plug

code	T1	T2
Plug	Round plug	Flower plug

■ Outline dimension drawing



Specification and dimension list

Unit: mm

Suction cup specification	Material of suction cup	Installation method	parameter					
			D	H	h	L _g	G	S
GBLP-30	S FS	02M	30	36.5	6	9	G1/4	19
GBLP-40		03M	40	40	6	10	G3/8	22
GBLP-50		04M	50	55	6	10	G1/2	28

Specification selection list

Unit: mm

Connector specification	Material of suction cup	02M	03M	04M	T1	T2
		G1/4External thread	G3/8External thread	G1/2External thread	Round plug	Flower plug
GBLP-30	S FS	●	—	—	○	●
GBLP-40		—	●	—	●	●
GBLP-50		—	—	●	○	●

Note: the default specification is "●", the optional specification is "○", and the non-optional specification is "—"

Packing method	date of delivery
1pcs/bag	The delivery period is generally 1-3 working days



Ordering example

GBLP30-S
GBLP-50-FS-04M-T2



It is most suitable for adsorbing irregular packaging, frozen food bags, water bags, etc